



Smallest jamb depth available on a double rabbet mullion is 4 3/8" (3 3/8" Wall Dimension).

Smallest jamb depth available on a single rabbet mullion is 3 1/4" (2 1/4" Wall Dimension).

Largest jamb depth available is 52 7/8" (51 7/8" Wall Dimension).

Smallest face dimension available on a double rabbet mullion tube is 3/4".

Smallest face dimension available on the door / glass rabbet side of a single rabbet mullion tube is 3/4".

Smallest face dimension available on the soffit side of a single rabbet mullion tube is 2".

Largest face dimension available on a mullion tube is 52 7/8".

Single rabbet mullion tubes may be used with double rabbet frame profiles within a single welded unit.

Mullion tubes are available in many custom configurations.

UL Fire Rated welded units with glass or panels:

- Smallest jamb & head face dimension allowed is 1 1/4".
- Largest jamb face dimension allowed is 4".
- Largest head face dimension allowed is 6".
- Largest jamb depth allowed is 14".
- 3/4" Stops are required at each glass section if one or more sections exceeds 500 square inches.

Face dimensions shown on drawing are typical dimensions to be provided unless otherwise specified by customer.

JR METAL FRAMES MANUFACTURERS OF STANDARD AND CUSTOM HOLLOW METAL FRAMES AND DOORS 287 Oakland Road, Belgrade, Maine 04917 USA Office 207-465-9066 Fax: 207-465-9452			
QUALITY SINCE 1981	Title: Mullion Tube Profile		
	Revision: #1	Revision Date: 11-07-07	Drawing Number: DD0009
Original Date: 09-27-07	Scale: Do not scale this drawing	Sheet: 34 of 55	