Untitled Document file:///C:/DW-CIB/Insul3.html

Home | About JR | Contact Us

Specifications

LEED/GREEN

Installation

Applications



Insul-hold coils come in 100' Rolls

METAL FRAMES CUSTOM MADE METAL DOORS AND FRAMES

It's Easy Being Green with JR's Insul-Hold


Insul-Hold is a support system for all types of rigid and fiberglass insulation products. Designed to anchor and hold most types of insulation in the correct position thereby preserving the R-value of the insulating product. Whether used to prevent heat loss or promote efficient cooling, Insul-Hold assures maximum effectiveness of any insulating product. Insul-Hold also doubles as horizontal bracing which prevents insulation from falling too deeply into the wall cavity. Suitable for use in wood frame, steel building, or masonry construction of interior or exterior walls, ceilings and crawl spaces and in basements, it provides support even where sheathing is not required. Insul-Hold is ideal for use in retrofitting buildings as well as new construction to Green and LEED standards. Easy to use Insul-Hold saves time, energy and money.

Nothing Holds Like Insul-Hold

When used as specified*, Insul-Hold is cost effective as it dramatically reduces the time it takes to install insulation as compared to the conventional method. Insul-Hold eliminates the frustrations of sagging and falling insulation and avoids costly, insulation related call backs. When Insul-Hold is used, insulation immediately hangs correctly and stays in place.

Product Description

Fabricated with 20 gauge galvannealed steel and packaged in 100 foot rolls weighing approximately 13 lbs, *Insul-Hold never rusts*. As a time savings convenience, the 100 foot rolls are



delivered in self-dispensing boxes, no larger than a pizza box for ease of handling and storage. Insul-Hold is pulled out of the box as needed; there is no need to pre-cut and measure, no struggling with entangled lengths, installation is quick and easy. The rolls are pre-punched every 8 inches with a uniquely designed arrow for quick and easy fastening to stud layout. The pre-punched arrows remain flat until they are folded out, just prior to hanging insulation. Insul-Hold lies flat, making it easy to cut with tin snips and especially safe to use. Additionally, the 3" arrow lengths may be varied by bending at different points on the arrow, making them ideal for use with various insulation densities and thicknesses. The unique arrow design allows insulation to be slipped easily onto the arrows, but prevents it from slipping off. When used properly*, the unique arrow penetrates without protruding through the insulation preventing thermal short-circuiting, and it does not break through the vapor barrier preserving the R-value. Insul-Hold can be used on virtually any surface.

Insul-Hold is a Division of JR Metal Frames Manufacturing, Inc.

1 of 2 2/7/2012 9:44 AM

Untitled Document file:///C:/DW-CIB/Insul3.html

Copyright 2011 J R Metal Frames Maufacturing, Inc., All rights reserved

2 of 2